



# ci c20

em



# The professional single-phase trolley pressure washer that is compact and robust

The CI C20 EM trolley cold pressure washer stands out for being compact and robust. It is the professional power washer that offers the perfect combination of high technical performance with user-friendliness and easy maintenance.

Equipped with a trolley that has a robust, resistant structure thanks to its large back wheels with rubber treads and a practical aluminium handle, the CI C20 EM is solid but also agile and easy to move.

Its excellent performance makes the CI C20 EM a professional pressure washer that is ideal for removing the most stubborn, caked on dirt and for frequent, extended jobs. It is therefore the perfect power washer for the handicraft, automotive, industrial, food, and agricultural sectors.

## THE ADVANTAGES OF CI C20 EM

Many are the benefits CI C20 EM can offer:

- Pressure washer with robust trolley and two large back wheels with wide rubber treads that facilitate manoeuvrability and transportability
- Painted steel frame and practical handle to facilitate movement
- Powerful induction motor that makes the pressure washer highly performing, efficient and reliable
- The single-phase electric induction motor with heat projection guarantees high reliability and allows the power washer to work uninterrupted for hours without breaks, withstanding even transient power spikes or surges optimally
- Ceramic 3-piston pump with crank-rod system and brass head for high performance
- Automatic safety valve with pressure shut-off at pump head
- Adjustable pressure
- Built-in manometer
- Built-in adjustable detergent suction
- Practical built-in 3-litre detergent tank
- Inspectionable water feed filter
- 10-metre reinforced high pressure tube
- Stop&Go: when the machine is temporarily idle, it stops so as to optimize consumption and reduce waste
- Comes with professional accessories: high pressure spray gun, wand with interchangeable nozzles, reinforced tube
- Black nozzle for low pressure
- Red nozzle for high/low pressure and straight jet – 0°
- Yellow nozzle for high/low pressure and fan jet – 15°
- Green nozzle for high/low pressure and fan jet – 25°
- White nozzle for high/low pressure and fan jet – 40°
- Accessory holder and tube storage on the back

TECHNICAL DESCRIPTION		CI C20 EM
Max pressure	bar/psi	150/2200
Max flow rate	l/h	630
Type	-	cold water
Power consumption	KW	3,0
Power supply	V/Hz	230/50
Motor	type/hp	single-phase electric induction
Rotation speed	rpm	1450
Pump	type	ceramic piston with crank-rod system
Pump head	material	brass
Net weight	Kg	49,7
Machine dimensions (Lxhxw)	mm	460x810x460



COMAC S.p.A. Via Maestri del Lavoro, 13 - 37059 Santa Maria di Zevio - Verona - ITALY  
Tel. 045 8774222 - [www.comac.it](http://www.comac.it) - [com@comac.it](mailto:com@comac.it)

Comac S.p.A. org. cert. ISO 9001:2015, ISO 14001:2015, ISO 45001:2018, SA 8000:2014

