



ci C30

EM



The professional three-phase trolley pressure washer that is compact and robust

The CI C30 EM is a **trolley cold pressure washer** designed to be compact yet robust. It is a professional power washer capable of offering the perfect combination of performance, user-friendliness and easy maintenance.

The CI C30 EM's robust metal trolley and two large wheels with rubber treads make it a solid **power washer** that is still easy to move.

High reliability and excellent performance allow the CI C30 EM to be the ideal **professional cold pressure** washer for intensive use and long jobs. It is therefore perfect for the food, agricultural, industrial, automotive and handicraft sectors.

THE ADVANTAGES OF CI C30 EM

Many are the benefits CI C30 EM can offer:

- Pressure washer with robust trolley and two large back wheels with wide rubber treads that facilitate manoeuvrability and transportability
- Painted steel frame and practical handle to facilitate movement
- Powerful induction motor that makes the pressure washer highly performing, efficient and reliable
- The three-phase electric induction motor with heat projection guarantees high reliability and allows the power washer to work uninterrupted for hours without breaks, withstanding even transient power spikes or surges optimally
- Ceramic 3-piston pump with crank-rod system and brass head for high performance
- Automatic safety valve with pressure shut-off at pump head
- Adjustable pressure
- Built-in manometer
- Flanged adjustment valve
- Built-in adjustable detergent suction
- Practical built-in 3-litre detergent tank
- Inspectionable water feed filter
- 10-metre reinforced high pressure tube
- Stop&Go: when the machine is temporarily idle, it stops so as to optimize consumption and reduce waste
- Comes with professional accessories: high pressure spray gun, wand with interchangeable nozzles, reinforced tube
- Black nozzle for low pressure
- Red nozzle for high/low pressure and straight jet – 0°
- Yellow nozzle for high/low pressure and fan jet – 15°
- Green nozzle for high/low pressure and fan jet – 25°
- White nozzle for high/low pressure and fan jet – 40°
- Accessory holder and tube storage on the back

TECHNICAL DESCRIPTION		CI C30 EM
Max pressure	bar/psi	200/2900
Max flow rate	l/h	900
Type	-	cold water
Power consumption	KW	7,4
Power supply	V/Hz	400/50
Motor	type/hp	three-phase electric induction
Rotation speed	rpm	1450
Pump	type	ceramic piston with crank-rod system
Pump head	material	brass
Net weight	Kg	54,8
Machine dimensions (Lxhxw)	mm	670x900x540



COMAC S.p.A. Via Maestri del Lavoro, 13 - 37059 Santa Maria di Zevio - Verona - ITALY
Tel. 045 8774222 - www.comac.it - com@comac.it

Comac S.p.A. org. cert. ISO 9001:2015, ISO 14001:2015, ISO 45001:2018, SA 8000:2014

